



Plus - Power Supply
The EXOGAL Comet Plus Power Supply gives you the power to squeeze out that last drop of performance from your Comet DAC! It provides plenty of power to stretch out and render the highest highs, drive the deepest bass, and let the Comet deliver the richest, most authentic sound stage of any DAC on the market.

Specifications

Input Voltage: 85 VAC to 264 VAC
AC Inlet: IEC320-C14
Output Power Rating: 25W
Output Voltage: 15 VDC
Output Current: 1.7Amps
Internal Capacitance: 85,000uF
Typical Output Noise: <400 uVpp
DC Cord Length: 5 ft (1.5m)
Dimensions (HWD):
2.25 x 6 x 6.5 in.,
(57.2 x 152.4 x 165mm)
Weight: 2 lbs (.91 kg)
Finish: Black
Includes: Auxiliary DC Power Jack

Comet Plus Digital to Analog Converter

The EXOGAL Comet is a high performance digital to analog audio converter (DAC). Just connect your computer, or other digital/analog source, and experience exceptional audiophile quality sound. The Comet DAC does everything you would expect a high-end DAC to do, including balanced and unbalanced analog outputs, digital volume control and asynchronous USB input. Audio signals are processed using EXOGAL up-sampling and filtering technology. The USB input can accept up to 32-bit/384kHz PCM data rates, DSD64, and DSD128 in DOP (DSD over PCM) format.



Features

- Designed for real-life listening with sound that's amazing, whatever the setting
- Asynchronous USB, AES/EBU, SPDIF, Toslink, and line level Analog inputs
- Direct connection analog outputs with 32-bit Digital Volume Control
- Analog Outputs: one pair balanced (XLR), one pair unbalanced (RCA), one stereo Headphone
- Single ended and balanced analog outputs can be used simultaneously
Single ended outputs can be programmed as stereo, or center/subwoofer operation
Single ended outputs have a programmable offset level from balanced outputs
- Controlled by the Exogal Remote App for Android phone or tablet (running 4.3 or higher with BLE support) or an iPad, iPhone (4 or newer), or iPod Touch
- Easy digital upgrades for hardware and software

	AES/EBU XLR	SPDIF BNC	Toslink	USB-B
16 Bit	X	X	X	X
24 Bit	X	X	X	X
32 Bit				X
32kHz	X	X	X	X
44.1kHz	X	X	X	X
48kHz	X	X	X	X
88.2kHz	X	X	X	X
96kHz	X	X	X	X
176.4kHz	X	X		X
192kHz	X	X		X
384kHz				X
DSD 64				X
DSD 128				X

Specifications

Digital Inputs: AES/EBU on XLR, SPDIF on 75Ohm BNC, Toslink, USB-B
Analog Input: One Pair Unbalanced RCA
Analog Outputs: One Pair Balanced (XLR), One Pair Unbalanced (RCA),
One Stereo Headphone (1/4" jack)
Weight: 9.2 lbs, 4.2 kg
Dimensions (HWD): 1.875 x 11.5 x 7.45 in., (47.6 x 292 x 190mm)
Finish: Anodized Aluminum or Black

USB System Requirements

Apple: OS 10.6.4 or higher - No driver needed
PC: Windows XP SP3, Windows Vista SP2 or higher, Windows 7, Windows 8